

Docket No. RSW9-2000-0090-US1

**CLAIMS:**

What is claimed is:

1 1. A method in a data processing system for managing a  
2 request including a session identification, comprising:  
3 calculating a first value based on the session  
4 identification; and  
5 routing the request to a server based on the first  
6 value.

1 2. The method of claim 1, wherein the step of  
2 calculating a first value comprises performing a hash  
3 function on the session identification.

1 3. The method of claim 2, wherein the step of routing  
2 the request to a server comprises:  
3 performing a modulus function on the first value to  
4 form a first integer; and  
5 selecting a server based on the first integer.

1 4. The method of claim 3, wherein the step of selecting  
2 a server comprises looking up the server in a look-up  
3 table using the first integer.

1 5. The method of claim 1, wherein the step of routing  
2 the request to a server comprises:  
3 selecting a first server based on the first value;  
4 determining whether the first server is functional;  
5 and

Docket No. RSW9-2000-0090-US1

6 routing the request to the first server in response  
7 to the first server being functional.

1 6. The method of claim 5, further comprising:  
2 calculating a second value based on the first value  
3 in response to the first server being non-functional; and  
4 routing the request to a second server based on the  
5 second value.

1 7. The method of claim 5, wherein the step of determining  
2 whether the first server is functional comprises using a  
3 look-up table.

1 8. A method in a data processing system for routing a  
2 request to one of a number of servers, comprising:  
3 receiving a request including a session  
4 identification;  
5 performing a hash function on the session  
6 identification to form a hash value;  
7 performing a modulus function on the hash value to  
8 form an integer; and  
9 routing the request to one of the number of servers  
10 based on the integer.

1 9. The method of claim 8, wherein the integer is between  
2 zero and the number of servers minus one.

1 10. The method of claim 8, wherein the step of routing  
2 the request comprises looking up the server in a look-up  
3 table using the integer.

Docket No. RSW9-2000-0090-US1

1 11. An apparatus for managing a request including a  
2 session identification, comprising:  
3 calculation means for calculating a first value  
4 based on the session identification; and  
5 routing means for routing the request to a server  
6 based on the first value.

1 12. The apparatus of claim 11, wherein the calculation  
2 means comprises hash means for performing a hash function  
3 on the session identification.

1 13. The apparatus of claim 12, wherein the routing means  
2 comprises:  
3 modulus means for performing a modulus function on  
4 the first value to form a first integer; and  
5 selection means for selecting a server based on the  
6 first integer.

1 14. The apparatus of claim 13, wherein the selection  
2 means comprises table means for looking up the server in  
3 a look-up table using the first integer.

1 15. The apparatus of claim 11, wherein the routing means  
2 comprises:  
3 selection means for selecting a first server based  
4 on the first value;  
5 determining means for determining whether the first  
6 server is functional; and

Docket No. RSW9-2000-0090-US1

7 means for routing the request to the first server in  
8 response to the first server being functional.

1 16. The apparatus of claim 15, further comprising:  
2 means for calculating a second value based on the  
3 first value in response to the first server being non-  
4 functional; and  
5 means for routing the request to a second server  
6 based on the second value.

1 17. The apparatus of claim 15, wherein the determining  
2 means uses a look-up table.

1 18. An apparatus for routing a request to one of a  
2 number of servers, comprising:  
3 a processor; and  
4 a memory electrically connected to the processor,  
5 the memory having stored therein a program to be executed  
6 on the processor for performing:  
7 receiving a request including a session  
8 identification;  
9 performing a hash function on the session  
10 identification to form a hash value;  
11 performing a modulus function on the hash value  
12 to form an integer; and  
13 routing the request to one of the number of  
14 servers based on the integer.

1 19. The apparatus of claim 18, wherein the integer is  
2 between zero and the number of servers minus one.

Docket No. RSW9-2000-0090-US1

1 20. The apparatus of claim 18, wherein the step of  
2 routing the request comprises looking up the server in a  
3 look-up table using the integer.

1 21. A distributed processing system comprising:  
2 a client computer;  
3 a first application server;  
4 a second application server;  
5 a web server, connected to the client computer, the  
6 first application server, and the second application  
7 server, the web server for routing a request from the  
8 client computer to one of the first application server  
9 and the second application server; and  
10 a database, connected to the first application  
11 server and the second application server, for storing  
12 session data associated with the request.

1 22. The system of claim 21, wherein the web server  
2 routes the request to the first application server and  
3 the first application server establishes a session with  
4 the client computer and generates a session  
5 identification.

1 23. The system of claim 22, wherein the first  
2 application server stores the session data in the  
3 database.

1 24. The system of claim 23, wherein the web server  
2 receives a second request including the session

Docket No. RSW9-2000-0090-US1

3 identification, performs a calculation on the session  
4 identification to form a value and routes the request to  
5 the second application server based on the value.

1 25. A computer program product, in a computer readable  
2 medium, for managing a request including a session  
3 identification, comprising:  
4 instructions for calculating a first value based on  
5 the session identification; and  
6 instructions for routing the request to a server  
7 based on the first value.

1 26. A computer program product, in a computer readable  
2 medium, for routing a request to one of a number of  
3 servers, comprising:  
4 instructions for receiving a request including a  
5 session identification;  
6 instructions for performing a hash function on the  
7 session identification to form a hash value;  
8 instructions for performing a modulus function on  
9 the hash value to form an integer; and  
10 instructions for routing the request to one of the  
11 number of servers based on the integer.